

## AC15" koax1.4"

### Two-way loudspeaker system



The AC15"koax1.4" is a compact,15" LF driver and 1.4" exit HF driver,2-way,highly weather-resistant full range loudspeaker with high SPL,the body is made of engineering plastic injection molding.The system conforms to IP56 international standard.

#### FEATURES

- Highly weather-resistant IP56 rating
- Engineering plastic injection molding
- High SPL
- Horn loaded design for HF driver and LF driver
- Good used for sports facilities, stadiums, water parks, and a wide variety of other outdoor venue types.



#### Overall dimensions



#### Technical specifications

FREQUENCY RESPONSE(-3dB)	50Hz-18kHz
DRIVERS	1×15" (385mm)/3" voice coil LF 1×1.4" (36mm)/3" voice coil HF
POWER	600W RMS, 2400W peak
SENSITIVITY	103 dB 1 watt/1 metre
MAXIMUM SPL	129 dB continuous, 135dB peak
IMPEDANCE	8 ohms nominal
DISPERSION(-6 dB)	60° ×40°
CROSSOVER	1.5 kHz passive
INPUT CONNECTORS	covered barrier strip terminals
DIMENSIONS	(W)499mm×(H)500mm×(D)598mm
WEIGHT	28.5kg

