

ACK1502neo


Two-way Loudspeaker System

The ACK1502neo is a 15", light weight, high SPL, two way full range speaker with bright and powerful sound. Unit configuration: 1×15" high power neodymium mid-bass unit, 1×1.4" exit throat 75mm neodymium composite diaphragm HF driver with 90°×40° rotatable horn. The cabinet is made of multilayer composite plywood with wear-resistant polyurea paint.

Features

- High quality unit configuration, high strength plywood housing
- Small size, light weight, easy handling and fixed installation
- Multi-hanging points and support, easy and quick operation
- Applications: large-scale indoor sound reinforcement, multifunction halls, high-end hotel clubs, touring, band reinforcement and monitor speaker

Overall dimensions



Technical specifications

FREQUENCY RESPONSE	45Hz-18kHz
DRIVERS	1×15"(385mm)/4" voice coil LF 1×1.4"(36mm)/ 3"voice coil HF
RATED POWER	1200W RMS,4800W peak
SENSITIVITY	98 dB 1 watt/1 metre
MAXIMUM SPL	126 dB continuous,132 dB peak
IMPEDANCE	8 ohms nominal
DISPERSION(-6 dB)	90°×40°
CROSSOVER	1.5 kHz passive
CONNECTORS	2×Speakon NL4
DIMENSIONS	(W)430mm×(H)712mm×(D)446mm
WEIGHT	26kg/pc

